



ALL AUTOMOTIVE & INDUSTRIAL OIL, GEAR OIL,
ENGINE OIL, BRAKE FLUID, Coolant & Greases



Different. & Better. High Performance Lubricants



4T Plus, SAE 20W-40 BIKE ENGINE OIL

4T Plus, SAE 20W-40 is a universal oil for Engine, Clutch and Gear of Motorcycle. It is formulated to meet the performance requirements of OEMs. This is an all-season engine oil specially developed to meet the friction requirements of the latest high performance air-cooled four stroke motorcycle.

- Longer replacement period.
- Lowers engine maintenance cost.
- Excellent wet clutch performance.
- Excellent wear & oxidation protection.
- Resist gear pitting.

PACK SIZE : 210 ltr, 50 ltr, 1 ltr, 900 ml, 800ml



4T Plus, SAE 10W-30 BIKE ENGINE OIL

4T Plus SAE 10W-30 is a universal oil for engine, clutch and gear of motorcycle. It is formulated to meet the performance requirements of OEMs. This is an all-season engine oil specially developed to meet the friction requirements of the latest high performance air-cooled four stroke motorcycle.

- Longer replacement period.
- Lowers engine maintenance cost.
- Excellent wet clutch performance.
- Excellent wear & oxidation protection.
- Resist gear pitting.

PACK SIZE : 210 ltr, 50 ltr, 1 ltr, 900 ml, 800ml

SAE 20W-40 ENGINE OIL | MULTIGRADE

SAE 20W-40 Engine Oil meets the following specifications. IS:13656, US:MIL-L-2014 B and API CF-4, HD Type 3. Engine oil multigrade oils besides meeting the characteristics and performance of engine Oils provides ease in cold starting due to their very high viscosity index.

These oils are ideal for use in all seasons in petrol engines naturally aspirated diesel engines operating under severe duty and supercharged diesel engines.

PACK SIZE : 210 ltr, 50 ltr, 20 ltr, 10 ltr, 7.5 ltr, 5 ltr, 3.5 ltr, 3 ltr, 1 ltr, 500 ml



TURBO POWER, SAE 15W-40 ENGINE OIL

SAE 15W-40 Engine Oils meets the following specifications.

US : MIL-L-2104 E and API CH-4.

Better protection of cam & valve train.

Excellent engine protection & long engine life.

Lesser all consumption.

Recommended for Turbo charged engine for Trucks, Buses, LCVs, Tractors & Jeeps.

PACK SIZE : 210 ltr, 50 ltr, 15 ltr, 7.5 ltr, 10 ltr, 5 ltr, 3.5 ltr, 3 ltr, 1 ltr, 500 ml

SAE 5W-30 ENGINE OIL | MULTIGRADE

SAE 20W-40 Engine Oil meets the following specifications. IS:13656, US:MIL-L-2014 B and API CF-4, HD Type 3. Engine oil multigrade oils besides meeting the characteristics and performance of engine Oils provides ease in cold starting due to their very high viscosity index.

These oils are ideal for use in all seasons in petrol engines naturally aspirated diesel engines operating under severe duty and supercharged diesel engines.

PACK SIZE : 210 ltr, 50 ltr, 20 ltr, 10 ltr, 7.5 ltr, 5 ltr, 3.5 ltr, 3 ltr, 1 ltr, 500 ml



Different & Better High Performance Lubricants



SAE 20W-50, ENGINE OIL

DESCRIPTION : Exide SAE 20W-50 is multigrade gas engine oil, meeting performance requirements. It is specially developed for vehicles operating on CNG/LPG with dual fuel kit i.e. suitable for operating on petrol/diesel also. It is formulated with high viscosity index base oil and specially selected additives.

PRODUCT FEATURES : Low ash contents reduces the formation of lacquer / sludge in the engines. Good anti-scuffing properties. Protect the engine from Nitrates & Oxide formation.

APPLICATION: Recommended for all Cars, Taxi, 3 Wheelers and Commercial Vehicles, Running on CNG/LPG. Also suitable for vehicles engines running on petrol/diesel.

PACK SIZE : 210 ltr, 50 ltr, 20 ltr, 10 ltr, 5 ltr, 3.5 ltr, 3 ltr, 1 ltr, 500 ml



COOLANT

Concentrate 1:4 is mono ethylene glycol based anti-freeze coolant using corrosion compound of hybrid additives technology for approved ARIELAB PUNE.

Direction for use : Dilute 1 part of TURBO JETPLUS coolant with 4 part of water.

Benefits : • Good chemical stability at high boiling point. • Easy water mixability. • Acts as anti-freeze agents in cold season. • Foam inhibitor reduces air and foam in the cooling system. • Excellent anti-freeze quality. • Effective control of corrosion.

Applications : Concentrate 1:4

Caution : Keep out of reach of children. Do not add coolant when the engine is hot

It meets : JIS K-2234-94

PACK SIZE : 50 ltr, 20 ltr, 5 ltr, 3.5 ltr, 3 ltr, 1 ltr, 500 ml



EP-90 / EP-140 / 80W-90 / 85W-140 GEAR OIL

GEAR OIL is multipurpose sulphur phosphorous based extreme pressure superior quality heavy-duty gear oil. It has been formulated with advance EP additive to provide extreme pressure, wear corrosion, oxidating, anti foaming. It also can contain pour point depressant to prevent the lubricant from channeling at low temperature.

RECOMMENDATIONS : for hypoid spiral bevel or worm gear transmission system for Car, Buses, Trucks and Tractors requiring EP-type lubricants.

PERFORMANCE STANDARDS : • API GL-4 & GL-5/IS-1118-1992 • US Military MIL-L-2105D • UK Defece CS 3000B.

PACK SIZE : 210 ltr, 50 ltr, 20 ltr, 10 ltr, 5 ltr, 1 ltr, 500 ml



PUMP SET OIL, PSO SAE 20W-40

PUMP SET OIL - API SC/CC , PSO SAE 20W-40 is a high quality cranks case oil for petrol & diesel engines. It has excellent detergent - dispersant properties that ensure long life. It is found extremely suitable in all weather conditions and all season of mansoon, summer and winter. Widely acceptable across different pump application in variety of farm lands.

ADVANTAGES : • Excellent detergent and dispersant properties to Increase engine life. • Suitable for all weather and all seasons. • Provides smother operation to a variety of different pump applications.

PACK SIZE : 5 ltr, 3.5 ltr, 3 ltr, 1 ltr

UTTO, WET BRAKE OIL

UTTO is a Universal Tractor Transmission Oil (UTTO) developed to meet the diverse performance requirements of farm tractor lubricants such as the controlled friction requirement of power take off clutch and wet brakes, suppression of wet brake noise, good filterability and antifoam characteristics, protection against rust and corrosion and adequate EP and antiwear properties for maximum durability of the transmission, differential and final drive.

PACK SIZE : 50 ltr, 20 ltr, 10 ltr, 5 ltr



Different & Better High Performance Lubricants



HYDRAULIC OIL, 32 / 46 / 68

Superior quality multipurpose hydraulic oil ideally suitable for all type of hydraulic machines and equipments operating on mild and extreme pressure conditions.

- Provides excellent wear protection ensuring longer equipment life.
- Provides outstanding protection against oxidation.
- Provides superior deaeration Properties.
- Possesses very good chemical stability leading to longer oil service life.

PACK SIZE : 210 ltr, 50 ltr, 20 ltr, 10 ltr, 5 ltr, 1 ltr



AP-3 GREASE (MULTI-PURPOSE GREASE)



AP-3 GREASE is a premium quality multi functional long life lithium soap all purpose grease having a high value of drop point good thermal & structural stability, excellent load bearing capacity & improved anti-wear corrosion property.

RECOMMENDED for heavy duty automobile & industrial ball & roller bearing, wheel & motor bearing.

SPECIFICATION : IS-7623-1993, NLGI-3

PACK SIZE : 180 kg, 18 kg, 10 kg, 7 kg, 5 kg, 3 kg, 2 kg, 1 kg, 500 gm

AP-LR GREASE (LONG LIFE GREASE)

AP-LR ALL PURPOSE LONG LIFE GREASE is a premium quality specially formulated lithium based all purpose grease, fortified with EP additives which provides re-lubrication after under ideal road condition. It has good thermal, chemical and structural stability including water wash out properties.

RECOMMENDED FOR : All Trucks, Buses, tractors, Cars, etc.

APPLICATIONS : • Lubrication of plain as well as anti-friction bearings in automotive, earth moving equipment, mining equipment and general industrial machineries. • Heavy duty ball and roller bearings of steel rolling mills, operating under adverse conditions. • Universal joints and spline shafts working under heavy torque or with acute transmission angles.

PACK SIZE : 180 kg, 18 kg, 10 kg, 7 kg, 5 kg, 3 kg, 2 kg, 1 kg, 500 gm



GEL GREASE



- Excellent & buttery transparent look & feel.
- High water washout drain interval of 75,000 kms.
- Excellent increased thermal stability compared to normal AP-3 Grease.
- Superior wear & corrosion protection.
- Excellent adhesion/tacky property.
- Protects components against corrosion & wear, therefore, enhanced bearing life.
- Technical specification : NLGI-3

PACK SIZE : 180 kg, 18 kg, 10 kg, 7 kg, 5 kg, 3 kg, 2 kg, 1 kg, 500 gm

Manufactured by :
TURBOJET OIL AND POWER INDUSTRY PVT. LTD.

Mumbai Office : Plot No.-108, Survey No.-108/6, Aml Industrial Estate,
Silvassa, Dadra & Nagar Haveli (Maharashtra)-396230 India.

Bihar Head Office : Kharanza Road, Saguna More,
Danapur Cantt Patna Bihar - 801503

E-mail: info@turbojetoilindustry.com | www.turbojetoilindustry.com
Customer Care No.: +919155620400

